

STALKER® Pole Mounted Message Display (PMMD)

DISPLAY

Display range:	Up to 99 (199 option)
Display units:	mph or km/h
Character size:	15 inches (38 cm)
Message sign character size:	5 x 3 inches
Display color:	Amber on black background
Speed sign character type:	7-segment, 32 high-intensity LEDs per segment
Message sign character type:	16-segment, 4-8 high-intensity LEDs per segment
Intensity	Adapts to ambient light conditions
Speed alert:	Flashing
Speed hold time:	2 seconds standard, configurable

RADAR PERFORMANCE

Speed range:	1-200 mph (321.9 km/h)
Speed resolution:	1 mph (1 km/h)
Distance range:	1000 feet (304.8 m)
Speed accuracy:	± 0.5 mph ± 0.3% (± 0.8 km/h ± 0.3%)
Configuration:	Fully configurable with dedicated RS-232 port

POWER OPTIONS

Input options:	110 or 220 AC.
Power usage:	7 watts standby 48 watts typical display 72 watts peak

PHYSICAL

Size	52 x 36.5 x 2.3 inches (132 x 92.7 x 6 cm)
Housing Material:	Aluminum
Weight:	40 lbs. (18 kg)

ENVIRONMENTAL

Operating temperature:	-22° to 120° F (-30° to 49° C) Vented weather resistant housing
-------------------------------	--